

Chapter 18: PHP

CS 80: Internet Programming

Instructor: Mark Edmonds

PHP

- Extremely common
- Open-source
- Platform independent

Preliminaries

- PHP handles client requests
- PHP is embedded into HTML documents, but executes on the server *before* the HTML document is delivered to the client
- PHP files have the extension .php

Preliminaries

- php code resides between <?php /*PHP code */?>
 - Single line php comments start with //
 - Multiline comments are enclosed with /**/
- Statements terminated with a semicolon ; (required)

Variables

- Declared with \$name
 - name must start with a letter or underscore
 - name can only contain A–z, 0–9, and _

Variables

- Variables are case-sensitive
- Loosely typed
 - Similar idea as Javascript. Variables have types, but their type can change on the fly
 - In PHP, we have to explicitly change types

PHP Types

Type	Description
<code>int, integer</code>	Whole numbers (i.e., numbers without a decimal point).
<code>float, double, real</code>	Real numbers (i.e., numbers containing a decimal point).
<code>string</code>	Text enclosed in either single ('') or double ("") quotes. [Note: Using double quotes allows PHP to recognize more escape sequences.]
<code>bool, boolean</code>	<code>true</code> or <code>false</code> .
<code>array</code>	Group of elements.
<code>object</code>	Group of associated data and methods.
<code>resource</code>	An external source—usually information from a database.
<code>NULL</code>	No value.

Figure 1: PHP Types

Example: `first.php`

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.1: first.php -->
3 <!-- Simple PHP program. -->
4 <html>
5   <?php
6     $name = "Paul"; // declaration and initialization
7   ?><!-- end PHP script -->
8   <head>
9     <meta charset = "utf-8">
10    <title>Simple PHP document</title>
11   </head>
12   <body>
13     <!-- print variable name's value -->
14     <h1><?php print( "Welcome to PHP, $name!" ); ?></h1>
15   </body>
16 </html>
```

Important Notes

- Line 6 declares a php variable named `name` and sets it equal to Paul

- Line 14 prints text into the `<h1>` tag **before the file is served to the client**
 - Note that the value of `$name` is printed, not the string "`$name`"
 - Double quoted strings will have variables evaluated (called *interpolating* a variable)
 - Single quoted strings will have the entire string taken as a literal value (no interpolation)

Example: `data.php`

```
1  <!DOCTYPE html>
2  <!-- Fig. 19.3: data.php -->
3  <!-- Data type conversion. -->
4  <html>
5      <head>
6          <meta charset = "utf-8">
7          <title>Data type conversion</title>
8          <style type = "text/css">
9              p
10             {
11                 margin: 0;
12             }
13             .head
14             {
15                 margin-top: 10px;
16                 font-weight: bold;
17             }
18             .space
19             {
20                 margin-top: 10px;
21             }
22         </style>
23     </head>
24     <body>
25         <?php
26             // declare a string, double and integer
27             $testString = "3.5 seconds";
28             $testDouble = 79.2;
29             $testInteger = 12;
30         ?><!-- end PHP script -->
31         <!-- print each variable's value and type -->
32         <p class = "head">Original values:</p>
33         <?php
34             print( "<p>$testString is a(n) " . gettype( $testString ) . "</p>
35             >" );
```

```
35     print( "<p>$testDouble is a(n) " . gettype( $testDouble ) . "</p"
36         ">" );
37     print( "<p>$testInteger is a(n) " . gettype( $testInteger ) . "</
38         p>" );
39 ?><!-- end PHP script -->
40 <p class = "head">Converting to other data types:</p>
41 <?php
42     // call function settype to convert variable
43     // testString to different data types
44     print( "<p>$testString " );
45     settype( $testString, "double" );
46     print( " as a double is $testString</p>" );
47     print( "<p>$testString " );
48     settype( $testString, "integer" );
49     print( " as an integer is $testString</p>" );
50     settype( $testString, "string" );
51     print( "<p class = 'space'>Converting back to a string results in
52         $testString</p>" );
53     // use type casting to cast variables to a different type
54     $data = "98.6 degrees";
55     print( "<p class = 'space'>Before casting: $data is a " . gettype(
56         $data ) . "</p>" );
57     print( "<p class = 'space'>Using type casting instead:</p>
58         <p>as a double: " . (double) $data . "</p>" .
59         "<p>as an integer: " . (integer) $data . "</p>" );
60     print( "<p class = 'space'>After casting: $data is a " . gettype(
61         $data ) . "</p>" );
62 ?><!-- end PHP script -->
63 </body>
64 </html>
```

Types and Conversion

- `gettype` gets the type of the parameter
- `settype` changes the type of first parameter to the second parameter
- Using `settype` can result in data loss: values may be truncated
 - For example, converting 3.5 to an int yields 3, and converting the int back to a double yields 3
 - Same thing happens with strings "3.5 seconds" as a double becomes 3.5

Types and Conversion

- Casting
 - Creates a temporary copy of the data before converting it
 - Means we won't lose data
 - Useful when a different type is required for a specific operation, but you want to retain the original value

String Concatenation

- Same as with javascript, but the operator is .

Constant values

- Created with `DEFINE("NAME", value);`
- Not a variable, a constant
- Used by simply typing `NAME` where you want the value

Conditionals

- Basically the same as Javascript, but `else if` is `elseif` (another keyword)

Arithmetic Operators

- Same as Javascript

Example: operators.php

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.4: operators.php -->
3 <!-- Using arithmetic operators. -->
4 <html>
5   <head>
6     <meta charset = "utf-8">
7     <style type = "text/css">
8       p { margin: 0; }
9     </style>
10    <title>Using arithmetic operators</title>
11  </head>
12  <body>
```

```
13     <?php
14         $a = 5;
15         print( "<p>The value of variable a is $a</p>" );
16
17         // define constant VALUE
18         define( "VALUE", 5 );
19
20         // add constant VALUE to variable $a
21         $a = $a + VALUE;
22         print( "<p>Variable a after adding constant VALUE is $a</p>" );
23
24         // multiply variable $a by 2
25         $a *= 2;
26         print( "<p>Multiplying variable a by 2 yields $a</p>" );
27
28         // test if variable $a is less than 50
29         if ( $a < 50 )
30         {
31             print( "<p>Variable a is less than 50</p>" );
32         }
33
34         // add 40 to variable $a
35         $a += 40;
36         print( "<p>Variable a after adding 40 is $a</p>" );
37
38         // test if variable $a is 50 or less
39         if ( $a < 51 )
40         {
41             print( "<p>Variable a is still 50 or less</p>" );
42         }
43         elseif ( $a < 101 )
44         {
45             // $a >= 51 and <= 100
46             print( "<p>Variable a is now between 50 and 100, inclusive</p>" );
47         }
48         else // $a > 100
49         {
50             print( "<p>Variable a is now greater than 100</p>" );
51         }
52
53         // print an uninitialized variable
```

```
54     print( "<p>Using a variable before initializing: $nothing</p>" );
      // nothing evaluates to ""
55
56     // add constant VALUE to an uninitialized variable
57     $test = $num + VALUE;
58
59     // num evaluates to 0
60     print( "<p>An uninitialized variable plus constant VALUE yields
      $test</p>" );
61
62     // add a string to an integer
63     $str = "3 dollars";
64     $a += $str;
65     print( "<p>Adding a string to variable a yields $a</p>" );
66     ?><!-- end PHP script -->
67 </body>
68 </html>
```

Arrays

- PHP also supports arrays
 - Note that if an array does not exist, but is assigned, the array will be created
- PHP arrays may be *associative arrays*, meaning they have non-integer indices
 - E.g. you index an array by a name, or by student ID number (stored as a string)

Arrays

- `reset` resets the internal pointer of the array to the beginning of the array
 - `key` returns the index of the element pointed to by the internal pointer
 - `next` moves the internal pointer down one element of the array
- `foreach` is specifically for iterating through arrays
 - `as` divides the key/value (key is on the left, value is on the right)

Example: `array.php`

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.7: arrays.php -->
3 <!-- Array manipulation. -->
4 <html>
5 <head>
```

```
6 <meta charset = "utf-8">
7 <title>Array manipulation</title>
8 <style type = "text/css">
9 p
10 { margin: 0; }
11 .head { margin-top: 10px; font-weight: bold; }
12 </style>
13 </head>
14 <body>
15 <?php
16 // create array first
17 print( "<p class = 'head'>Creating the first array</p>" );
18 $first[ 0 ] = "zero";
19 $first[ 1 ] = "one";
20 $first[ 2 ] = "two";
21 $first[] = "three";
22 // print each element's index and value
23 for ( $i = 0; $i < count( $first ); ++$i )
24     print( "<p>Element $i is $first[$i]</p>" );
25 print( "<p class = 'head'>Creating the second array</p>" );
26 // call function array to create array second
27 $second = array( "zero", "one", "two", "three" );
28 for ( $i = 0; $i < count( $second ); ++$i )
29     print( "<p>Element $i is $second[$i]</p>" );
30 print( "<p class = 'head'>Creating the third array</p>" );
31 // assign values to entries using nonnumeric indices
32 $third[ "Amy" ] = 21;
33 $third[ "Bob" ] = 18;
34 $third[ "Carol" ] = 23;
35 // iterate through the array elements and print each
36 // element's name and value
37 for ( reset( $third ); $element = key( $third ); next( $third ) )
38     print( "<p>$element is $third[$element]</p>" );
39 print( "<p class = 'head'>Creating the fourth array</p>" );
40 // call function array to create array fourth using
41 // string indices
42 $fourth = array(
43     "January" => "first",
44     "February" => "second",
45     "March" => "third",
46     "April" => "fourth",
47     "May" => "fifth",
48     "June" => "sixth",
```

```
49     "July"  => "seventh",
50     "August" => "eighth",
51     "September" => "ninth",
52     "October"  => "tenth",
53     "November" => "eleventh",
54     "December" => "twelfth" );
55 // print each element's name and value
56 foreach ( $fourth as $element => $value )
57     print( "<p>$element is the $value month</p>" );
58?><!-- end PHP script -->
59 </body>
60 </html>
```

String Comparisons

- `strcmp` compares two strings.
 - returns -1 if the first string alphabetically precedes the second string
 - returns 0 if the two strings are equal
 - returns 1 if the first string alphabetically follows the second string
- Can also use relational operators
 - ==, !=, <, <=, >, >=

Example: compare.php

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.8: compare.php -->
3 <!-- Using the string-comparison operators. -->
4 <html>
5   <head>
6     <meta charset = "utf-8">
7     <title>String Comparison</title>
8     <style type = "text/css">
9       p { margin: 0; }
10      </style>
11    </head>
12    <body>
13      <?php
14        // create array fruits
15        $fruits = array( "apple", "orange", "banana" );
16        // iterate through each array element
```

```
17     for ( $i = 0; $i < count( $fruits ); ++$i )  
18     {  
19         // call function strcmp to compare the array element  
20         // to string "banana"  
21         if (strcmp( $fruits[ $i ], "banana" ) < 0) {  
22             print( "<p>" . $fruits[ $i ] . " is less than banana " );  
23         } elseif ( strcmp( $fruits[ $i ], "banana" ) > 0 ) {  
24             print( "<p>" . $fruits[ $i ] . " is greater than banana " );  
25         } else {  
26             print( "<p>" . $fruits[ $i ] . " is equal to banana " );  
27         }  
28         // use relational operators to compare each element  
29         // to string "apple"  
30         if ( $fruits[ $i ] < "apple" )  
31             print( "and less than apple!</p>" );  
32         elseif ( $fruits[ $i ] > "apple" )  
33             print( "and greater than apple!</p>" );  
34         elseif ( $fruits[ $i ] == "apple" )  
35             print( "and equal to apple!</p>" );  
36     } // end for  
37     ?><!-- end PHP script -->  
38     </body>  
39 </html>
```

Regular Expressions

- There is no escape from regular expressions
- php uses the `preg_match` function to search for a string with the specified pattern

Regular Expressions

- Important regex characters
 - `^` means beginning of line
 - `$` means end of line
 - `[]` denotes a bracket expression
 - * lists of characters
 - * can specify a range with -
 - * E.g. `[a-z]` are all characters a through z

Regular Expressions

- Quantifiers
 - specifies a quantity to match with the previous expression
 - * means 'zero or more times'
 - + means 'one or more times'
 - ? means 'zero or one times'
 - {n} means 'exactly n times'
 - {m,n} means 'between m and n times'
 - {n,} means 'n or more times'

Character Classes

Character class	Description
alnum	Alphanumeric characters (i.e., letters [a-zA-Z] or digits [0-9])
alpha	Word characters (i.e., letters [a-zA-Z])
digit	Digits
space	White space
lower	Lowercase letters
upper	Uppercase letters

Figure 2: Regex Character Classes

Example: `expression.php`

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.9: expression.php -->
3 <!-- Regular expressions. -->
4 <html>
5   <head>
6     <meta charset = "utf-8">
7     <title>Regular expressions</title>
8     <style type = "text/css">
9       p { margin: 0; }
10    </style>
11  </head>
12  <body>
```

```
13     <?php
14         $search = "Now is the time";
15         print( "<p>Test string is: '$search'</p>" );
16         // call preg_match to search for pattern 'Now' in variable search
17         if (
18             preg_match( "/Now/", $search )
19         )
20             print( "<p>'Now' was found.</p>" );
21             // search for pattern 'Now' in the beginning of the string
22             if (
23                 preg_match( "/^Now/", $search )
24             )
25                 print( "<p>'Now' found at beginning of the line.</p>" );
26                 // search for pattern 'Now' at the end of the string
27                 if (
28                     !preg_match( "/Now$/", $search )
29                 )
30                     print( "<p>'Now' was not found at the end of the line.</p>" );
31                     // search for any word ending in 'ow'
32                     if (
33                         preg_match( "/\b([a-zA-Z]*ow)\b/i", $search, $match )
34                     )
35                         print( "<p>Word found ending in 'ow': " .
36                             $match[ 1 ]
37                             . "</p>" );
38                         // search for any words beginning with 't'
39                         print( "<p>Words beginning with 't' found: " );
40                         while (
41                             preg_match( "/\b(t[:alpha:]+)\b/", $search, $match )
42                         )
43                         {
44                             print(
45                                 $match[ 1 ]
46                                 . " " );
47                             // remove the first occurrence of a word beginning
48                             // with 't' to find other instances in the string
49                             $search = preg_replace("/" . $match[ 1 ] . "/", "", $search);
50                         } // end while
51                         print( "</p>" );
52             ?><!-- end PHP script -->
53         </body>
54     </html>
```

Form Processing

Superglobal Arrays

- Special arrays that contain client information
- Client information includes:
 - Client's web browser
 - Data sent to the server by the client `$_GET` and `$_POST`
 - * E.g. if the user submits a form and it is posted to a script (remember the `action` attribute), then the information is available in the `$_POST` array
 - Cookies

Superglobal Arrays

Variable name	Description
<code>\$_SERVER</code>	Data about the currently running server.
<code>\$_ENV</code>	Data about the client's environment.
<code>\$_GET</code>	Data sent to the server by a get request.
<code>\$_POST</code>	Data sent to the server by a post request.
<code>\$_COOKIE</code>	Data contained in cookies on the client's computer.
<code>\$_GLOBALS</code>	Array containing all global variables.

Figure 3: Superglobal arrays

Example: `form.html`

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.13: form.html -->
3 <!-- HTML form for gathering user input. -->
4 <html>
5 <head>
6   <meta charset="utf-8">
7   <title>Sample Form</title>
8   <style type="text/css">
9     label {
10       width: 5em;
11       float: left;
12     }
```

```
13    </style>
14 </head>
15 <body>
16   <h1>Registration Form</h1>
17   <p>Please fill in all fields and click Register.</p>
18   <!-- post form data to form.php -->
19   <form method="post" action="form.php">
20     <h2>User Information</h2>
21     <!-- create four text boxes for user input -->
22     <div>
23       <label>First name:</label>
24       <input type="text" name="fname">
25     </div>
26     <div>
27       <label>Last name:</label>
28       <input type="text" name="lname">
29     </div>
30     <div>
31       <label>Email:</label>
32       <input type="text" name="email">
33     </div>
34     <div>
35       <label>Phone:</label>
36       <input type="text" name="phone" placeholder="(555) 555-5555">
37     </div>
38   <h2>Publications</h2>
39   <p>Which book would you like information about?</p>
40   <!-- create drop-down list containing book names -->
41   <select name="book">
42     <option>Internet and WWW How to Program</option>
43     <option>C++ How to Program</option>
44     <option>Java How to Program</option>
45     <option>Visual Basic How to Program</option>
46   </select>
47   <h2>Operating System</h2>
48   <p>Which operating system do you use?</p>
49   <!-- create five radio buttons -->
50   <p>
51     <input type = "radio" name = "os" value = "Windows" checked>
52       Windows
53     <input type = "radio" name = "os" value = "Mac OS X">Mac OS X
54     <input type = "radio" name = "os" value = "Linux">Linux
      <input type = "radio" name = "os" value = "Other">Other
```

```
55      </p>
56      <!-- create a submit button -->
57      <p>
58          <input type = "submit" name = "submit" value = "Register">
59      </p>
60  </form>
61  </body>
62 </html>
```

Form Processing

- Let's break down this form (it's been a while)
 - It uses the `POST` HTTP method to send data to `form.php`
 - It has the following inputs:
 - * `fname` (text)
 - * `lname` (text)
 - * `email` (text)
 - * `phone` (text)
 - * `book` (options)
 - * `os` (radio)

Form Processing

- So when we hit `Register` (the `submit` input), we will send the inputs to `form.php` using the `$_POST` superarray
 - Had we used the `GET` method we'd see values in the `$_GET` superarray
- The input names are the glue; the register an input to an entry in the superarray
 - This is why names mattered in chapter 2/3!!

Example: `form.php`

```
1  <!DOCTYPE html>
2  <!-- Fig. 19.14: form.php -->
3  <!-- Process information sent from form.html. -->
4  <html>
5      <head>
6          <meta charset = "utf-8">
7          <title>Form Validation</title>
8          <style type = "text/css">
```

```
9      p
10     { margin: 0px; }
11     .error
12     { color: red }
13     p.head { font-weight: bold; margin-top: 10px; }
14   </style>
15 </head>
16 <body>
17   <?php
18   // determine whether phone number is valid and print
19   // an error message if not
20   // regex looks for the following pattern "(###) ###-####"
21   if (!preg_match( "/^\\([0-9]{3}\\) [0-9]{3}-[0-9]{4}$/", $_POST["
22     phone"])) {
23     print( "<p class = 'error'>Invalid phone number</p>
24       <p>A valid phone number must be in the form
25         (555) 555-5555</p><p>Click the Back button,
26         enter a valid phone number and resubmit.</p>
27       <p>Thank You.</p></body></html>" );
28     die(); // terminate script execution
29   }
30 ?><!-- end PHP script -->
31 <p>
32   <!-- Access information from the submission using the $_POST
33       superarray -->
34   Hi <?php print( $_POST["fname"] ); ?>. Thank you for completing
35   the survey. You have been added to the
36   <?php print( $_POST["book"] ); ?>mailing list.
37 </p>
38 <p class = "head">
39   The following information has been saved in our database:
40 </p>
41 <p>Name: <?php print( $_POST["fname"] ); print( " " . $_POST["lname"
42     "] ); ?></p>
43 <p>Email: <?php print( $_POST["email"] ); ?></p>
44 <p>Phone: <?php print( $_POST["phone"] ); ?></p>
45 <p>OS: <?php print( $_POST["os"] ); ?></p>
46 <p class = "head">
47   This is only a sample form. You have not been added to a mailing
48   list.
49 </p>
50 </body>
```

```
47 </html>
```

Form Processing

- This validates the phone number!
 - Very important to validate your form inputs
- `die()` terminates the script, stops processing the form

Example: `data.html`

```
1  <!DOCTYPE html>
2  <!-- Fig. 19.15: data.html -->
3  <!-- Form to query a MySQL database. -->
4  <html>
5      <head>
6          <meta charset = "utf-8">
7          <title>Sample Database Query</title>
8      </head>
9      <body>
10         <h1>Querying a MySQL database.</h1>
11         <form method = "post" action = "database.php">
12             <p>Select a field to display:
13                 <!-- add a select box containing options -->
14                 <!-- for SELECT query -->
15                 <select name = "select">
16                     <option selected>*</option>
17                     <option>ID</option>
18                     <option>Title</option>
19                     <option>Category</option>
20                     <option>ISBN</option>
21                 </select>
22             </p>
23             <p>
24                 <input type = "submit" value = "Send Query">
25             </p>
26         </form>
27     </body>
28 </html>
```

Example: database.php

```
1 <!DOCTYPE html>
2 <!-- Fig. 19.16: database.php -->
3 <!-- Querying a database and displaying the results. -->
4 <html>
5   <head>
6     <meta charset = "utf-8">
7     <title>Search Results</title>
8     <style type = "text/css">
9       body
10      { font-family: sans-serif;
11        background-color: lightyellow; }
12      table { background-color: lightblue;
13        border-collapse: collapse;
14        border: 1px solid gray; }
15      td
16      { padding: 5px; }
17      tr:nth-child(odd) {
18        background-color: white; }
19    </style>
20  </head>
21  <body>
22    <?php
23      $select = $_POST["select"]; // creates variable $select
24      // build SELECT query
25      $query = "SELECT " . $select . " FROM books";
26      // Connect to MySQL
27      if ( !( $database = mysqli_connect( "localhost", "iw3http", "
28          password" ) ) )
29        die( "Could not connect to database </body></html>" );
30      // open Products database
31      if ( !mysqli_select_db($database, "products") )
32        die( "Could not open products database </body></html>" );
33      // query Products database
34      if ( !( $result = mysqli_query($database, $query) ) )
35      {
36        print( "<p>Could not execute query!</p>" );
37        die( mysqli_error() . "</body></html>" );
38      } // end if
39      mysqli_close( $database );
40    ?><!-- end PHP script -->
41    <table>
```

```
41      <caption>Results of "SELECT <?php print( "$select" ) ?>
42      FROM books"</caption>
43      <?php
44          // fetch each record in result set
45          while (
46              $row = mysqli_fetch_row( $result )
47          )
48          {
49              // build table to display results
50              print( "<tr>" );
51              foreach ( $row as $key => $value )
52                  print( "<td>$value</td>" );
53                  print( "</tr>" );
54          } // end while
55      ?><!-- end PHP script -->
56      </table>
57      <p>
58          Your search yielded <?php print( mysqli_num_rows( $result ) ) ?>
59          results.
60      </p>
61      <p>
62          Please email comments to <a href = "mailto:deitel@deitel.com">
63              Deitel and Associates, Inc.</a>
64      </p>
65      </body>
66  </html>
```

Database Processing

- This assumed we followed the Chapter 18 instructions for setting up MySQL
 - Includes source-ing the `products.sql` file
- `mysqli_connect` connects to the database
- `mysqli_select_db` opens the `products` database
- `mysqli_query` executes a MySQL query (what we learned about in chatper 18)
- `mysqli_close` closes the database

Database Processing

- `mysqli_fetch_row` returns an associative array containing the column of the current row from the query result

- The `key` is a unique column ID for the query
- `mysqli_fetch_assoc` returns an associative array where the column names are the keys storing the corresponding values
- `mysqli_num_rows` stores the number of rows in the query result

Cookies

- What is a cookie?
 - A piece of information from the server that resides on the client's computer
 - Maintains information about the client in between browsing sessions
 - * Cookies mean you don't have to login everytime you visit a website
 - * The cookie stores your login session (not password), basically meaning the website assumes you are the same user
 - You can disable cookies if you want, but it makes browsing significantly more annoying!
 - Can also track other client activity

Cookies

- Cookies are text files
 - Should never store passwords, credit card info, etc
- Cookies are only accessible by the website that placed the cookie on the client's computer
- Cookies have an expiration date - at which point the browser will delete the cookie off of the client's computer
- Cookies are sent back to the originating server when the user connects to that server

Example: `cookies.html`

```
1 <!DOCTYPE html>
2
3 <!-- Fig. 19.17: cookies.html -->
4 <!-- Gathering data to be written as a cookie. -->
5 <html>
6   <head>
7     <meta charset = "utf-8">
8     <title>Writing a cookie to the client computer</title>
9     <style type = "text/css">
10       label { width: 7em; float: left; }
11     </style>
12   </head>
```

```
13 <body>
14     <h2>Click Write Cookie to save your cookie data.</h2>
15     <form method = "post" action = "cookies.php">
16         <div><label>Name:</label>
17             <input type = "text" name = "name"></div>
18         <div><label>Height:</label>
19             <input type = "text" name = "height"></div>
20         <div><label>Favorite Color:</label>
21             <input type = "text" name = "color"></div>
22         <p><input type = "submit" value = "Write Cookie">
23     </form>
24 </body>
25 </html>
26
27 <!--
28 ****
29 * (C) Copyright 1992-2012 by Deitel & Associates, Inc. and
30 * Pearson Education, Inc. All Rights Reserved.
31 *
32 *
33 * DISCLAIMER: The authors and publisher of this book have used their
34 * best efforts in preparing the book. These efforts include the
35 * development, research, and testing of the theories and programs
36 * to determine their effectiveness. The authors and publisher make
37 * no warranty of any kind, expressed or implied, with regard to these
38 * programs or to the documentation contained in these books. The
39 * authors and publisher shall not be liable in any event for incidental or
40 * consequential damages in connection with, or arising out of, the
41 * furnishing, performance, or use of these programs.
```

```
41 ****  
42 -->
```

Example: cookies.php

```
1 <!-- Fig. 19.18: cookies.php -->  
2 <!-- Writing a cookie to the client. -->  
3 <?php  
4     define( "FIVE_DAYS", 60 * 60 * 24 * 5 ); // define constant  
5  
6     // write each form fields value to a cookie and set the  
7     // cookies expiration date  
8     setcookie( "name", $_POST["name"], time() + FIVE_DAYS );  
9     setcookie( "height", $_POST["height"], time() + FIVE_DAYS );  
10    setcookie( "color", $_POST["color"], time() + FIVE_DAYS );  
11 ?><!!-- end PHP script -->  
12  
13 <!DOCTYPE html>  
14  
15 <html>  
16     <head>  
17         <meta charset = "utf-8">  
18         <title>Cookie Saved</title>  
19         <style type = "text/css">  
20             p { margin: 0px; }  
21         </style>  
22     </head>  
23     <body>  
24         <p>The cookie has been set with the following data:</p>  
25  
26         <!-- print each form field's value -->  
27         <p>Name: <?php print( $_COOKIE["name"] ) ?></p>  
28         <p>Height: <?php print( $_COOKIE["height"] ) ?></p>  
29         <p>Favorite Color:  
30             <span style = "color: <?php print( $_COOKIE["color"] ) ?> ">  
31                 <?php print( $_COOKIE["color"] ) ?></span></p>  
32         <p>Click <a href = "readCookies.php">here</a>  
33             to read the saved cookie.</p>  
34     </body>  
35 </html>  
36
```

```
37 <!--
38 ****
39 * (C) Copyright 1992-2012 by Deitel & Associates, Inc. and
   *
40 * Pearson Education, Inc. All Rights Reserved.
   *
41 *
   *
42 * DISCLAIMER: The authors and publisher of this book have used their
   *
43 * best efforts in preparing the book. These efforts include the
   *
44 * development, research, and testing of the theories and programs
   *
45 * to determine their effectiveness. The authors and publisher make
   *
46 * no warranty of any kind, expressed or implied, with regard to these
   *
47 * programs or to the documentation contained in these books. The
   * authors *
48 * and publisher shall not be liable in any event for incidental or
   *
49 * consequential damages in connection with, or arising out of, the
   *
50 * furnishing, performance, or use of these programs.
   *
51 ****
52 -->
```

Cookies

- `setcookie` creates a cookie
 - First parameter is the name
 - Second parameter is the data
 - Third parameter is the expiration date
 - * If there is no expiration date, the cookie is a *session cookie*, which means it only exists during the current browsing session (when the user closes the browser, the session ends)

- * If a expiration date is specified, we call this cookie a *persistent cookie*
- Cookies are then accessible through the `$_COOKIE` superarray

Example: `readCookies.php`

```
1 <!DOCTYPE html>
2
3 <!-- Fig. 19.19: readCookies.php -->
4 <!-- Displaying the cookies contents. -->
5 <html>
6   <head>
7     <meta charset = "utf-8">
8     <title>Read Cookies</title>
9     <style type = "text/css">
10    p { margin: 0px; }
11    </style>
12  </head>
13  <body>
14    <p>The following data is saved in a cookie on your computer.</p>
15    <?php
16      // iterate through array $_COOKIE and print
17      // name and value of each cookie
18      foreach ($_COOKIE as $key => $value )
19        print( "<p>$key: $value</p>" );
20      ?><!-- end PHP script -->
21    </body>
22  </html>
23
24 <!--
25 ****
26 * (C) Copyright 1992-2012 by Deitel & Associates, Inc. and
27 * Pearson Education, Inc. All Rights Reserved.
28 *
29 *
30 * DISCLAIMER: The authors and publisher of this book have used their
31 * best efforts in preparing the book. These efforts include the
32 *
```

```
31 * development, research, and testing of the theories and programs
      *
32 * to determine their effectiveness. The authors and publisher make
      *
33 * no warranty of any kind, expressed or implied, with regard to these
      *
34 * programs or to the documentation contained in these books. The
      * authors *
35 * and publisher shall not be liable in any event for incidental or
      *
36 * consequential damages in connection with, or arising out of, the
      *
37 * furnishing, performance, or use of these programs.
      *
38 ****
39 -->
```